

RIVESTIMENTI IN BICOTTURA – WANDEFLIESEN ZWEIMAL-BRAND VERFAHREN –
DOUBLE FIRING WALL TILES – CARREAUX DE MUR EN BICUISSON

Serie : **WEISS LUX**

Formato : **25,0x60,0**

Gruppo BIII

	VALORI PRESCRITTI INTERNATIONALE NORMWERTE INTERNATIONAL STANDARD VALEURS	VALORI MEDI MITTELWERT AVERAGE VALUE VALEURS MOYENS	NORMA NORME NORM REGULATION
LUNGHEZZA E LARGHEZZA LAENGE UND BREITE DER FLIESE LENGHT AND WIDTH LONGUEUR ET LARGEUR	+/- 0,50%	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-2
SPESSORE STAERKE THICKNESS EPAISSEUR	+/- 10%	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-2
RETTILINEITA' DEGLI SPIGOLI GERADLINGKEIT STRAIGHTNESS EQUERRAGE DES ANGLES	+/- 0,3%	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-2
ORTOGONALITA' RECHTWINKLIGKEIT RECTANGULARITY ORTHOGONALITE	+/- 0,5%	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-2
PLANARITA' EBENFLACHIGKEIT WARPAGE PLANEITE	+/- 0,5% - 0,3% +/- 0,5% - 0,3% +/- 0,5%	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-2
ASSORBIMENTO D'ACQUA WASSWEAUFNAHME WATER ABSORPTION ABSORPTION D'EAU	>10%	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-3
RESISTENZA ALLA FLESSIONE BIEGEFESTIGKEIT BREAKING STRENGHT RESISTANCE A LA FLEXION	> 15 N/mm ²	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-4
FORZA DI ROTTURA BRUCHLAST IN N BREAKING FORCE IN N CHARGE DE RUPTURE	200 N	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-4
RESISTENZA AGLI SBALZI TERMICI TEMPERATURWECHSELBESTAENDIGKEIT THERMAL SHOCK RESISTANCE RESISTANCE AU CHOCS THERMIQUES	MPD	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-9
RESISTENZA AL CAVILLO HAARISS-BESTAENDIGKEIT CRAZING RESISTANCE RESISTANCE AUX CRAQUELLES	RICHIESTA REQUEST	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-11
RESISTENZA ALL'ATTACCO CHIMICO SAEUERE-LAUGEBESTAENDIGKEIT CHEMICAL RESISTANCE RESISTANCE A L'ATTAQUE CHIMIQUE	CLASSE GB min	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-13
RESISTENZA ALLE MACCHIE BESTAENDIGKEIT GEGEN FLECKEN STAIN RESISTANCE RESISTANCE AUX TACHES	CLASSE 3 min	CONFORME ENTSPRECHEND IN ACCORDANCE CONFORME	UNI EN ISO 10545-14

CERAMICHE MoMA S.p.A. SEDE LEGALE, STABILIMENTO ED UFFICI:

Via Panaria Bassa, 17/A – 41034 FINALE EMILIA (MO) ITALY – Tel. 0535.90401 – Fax 0535.90515

C.S. € 3.218.750 i.v. – R.E.A. MO n.158575 – Reg. Imprese MO/Cod. Fiscale 00330200361 – P.IVA IT00330200361 – N. Mecc. MO 003242

Sito Web: www.cermoma.com – E-mail: info@cermoma.com